




**Vickers**

**02-301682**

Industrial Valves - DG4V 3 8B VM U H7 61

Model Code: DG4V-3-8B-VM-U-H7-61  [Modify Configuration](#)

## Product Specifications

Feature	Code	Description
SEAL TYPE	-	VITON SEALS
FUNCTION	DG4V	DIRECTIONAL CONTROL VALVE, SUB PLATE MOUNTED & SOLENOID OPERATED.
INTERFACE	-3	ISO/DIS 4401-AB-03 D03
TYPE OF PERFORMANCE	-	HIGH PERFORMANCE
SPOOL TYPE	-8	TANDEM CENTRE 'P' TO 'T', OPEN CROSSOVER
SPOOL SPRING	B	SPRING OFFSET, END-TO-CENTRE
SOFT SHIFT OPTION	-	OMIT
SOFT SHIFT ORIFICE SIZE	-	NO ORIFICE
MANUAL OVERRIDE	-	PLAIN OVERRIDES IN SOLENOID ENDS ONLY
SOLENOID ENERGIZING IDENTITY AND FLAG SYMBOL	-VM	SOLENOID A IS AT PORT A END AND/OR SOLENOID B IS AT PORT B END, INDEPENDENT OF SPOOL TYPE (STANDARD ON #8 SPOOL TYPE)
SPOOL POSITION MONITORING SWITCH	-	NONE FITTED
ELECTRICAL CONNECTION	-U	ISO 4400 (DIN 43650) CONNECTOR
INDICATOR LIGHT	-	NONE
SURGE SUPPRESSOR/DAMPER	-	OMIT IF NOT REQUIRED
VOLTAGE OPTIONS	-H	24 VDC 30 WATT
TANK PRESSURE RATING	7	207 BAR (3000 PSI) FOR DC HIGH PERFORMANCE MODELS
DESIGN NUMBER	-61	61 DESIGN
SPECIAL FEATURES	-	NONE
P-PORT RESTRICTOR PLUG	-	NONE
A-PORT RESTRICTOR PLUG	-	NONE
B-PORT RESTRICTOR PLUG	-	NONE
T-PORT RESTRICTOR PLUG	-	NONE
VOLTAGE OPTION (COIL-LESS BUILD)	-	NOT SPECIFIED