

Pendulum level indicator



PF

Pendulum level indicator

..... PF Level indicator for vertical mounting



Use

Full indicator for powdery, granulated and grainy bulk goods with a max. grain size up to 100 mm and a bulk weight from 0.3 t/m³ ... 3.0 t/m³.

Preferred for mechanically filled silos and containers, for example with screw conveyors, feeders, elevators etc.

Function principle

The bulk goods, being dumped beside the pendulum, are moving the pendulum more and more aside, as the filling level increases. This movement activates the switch for the full indication. When the filling level falls, the pendulum moves back in the vertical position and the switch will be disengaged.

Suitable for all industrial fields.

..... Technical data

Materials

- ▶ housing aluminium
- ▶ sealing and anti-buckling protection NBR
- ▶ pendulum rod and cone aluminium or stainless steel

Signal contact

change-over contact, potentialfree

Capacity of the contact

4 A / 250 V AC

Ambient temperature

-20 °C ≤ Ta ≤ +70 °C

Bulk temperature

-25 °C ≤ Ta ≤ +80 °C

Type of protection

IP66

Maintenance

none

..... ATEX-Options

Ex types of protection

- ⚠ II 1/2D Ex ta/tb IIIC T80°C
- ⚠ II 2G Ex ib IIB T6

..... Function



MOLLET
Füllstandtechnik

Industriepark RIO 103 D-74706 Osterburken
Phone +49(0)6291 6440-0 Fax +49(0)6291 9846
info@mollet-gmbh.de www.mollet-gmbh.de