Instrument Data Sheet

Instrument Data Sheet			
General	1	Product	Belt Alignment Control
	2	Model Number	TA-2
	3	Manufacturer	Conveyor Components Company
	4		
Environment	5	Certified Ambient	40 °C [104 °F]
	ر	Temperature Rating	
	6	Functional Ambient	-50 to 40 °C [-58 to 104 °F]
		Temperature	
LIMITOTITIETIL	7	Enclosure Material	319 cast aluminum
	8	Enclosure Rating	NEMA Type 3S, 4, 4X, 5
	9	Mounting	3 holes at Ø ¹³ / ₃₂ " (Surface mount)
	10		
Switch	11	Switch Type	SPDT x 2
	12	Contact Type	Dry contact
	13	Contact Rating	20A @ 125V, 250V or 480V AC; 10A @ 125V AC inductive; 1 hp
			125V AC; 2 hp 250V AC, ½ A @ 125 V DC; ¼ A @250 V DC
	14	Electrical Action	Non-latching
	15	Electrical Connection	¾" NPT x 1
	16	Indicating Lamp	None
	17		
	18		
	19		
Actuator	20	Туре	Belt alignment control
	21	Mechanism	Sprung roller lever with rotating cam
	22	Non-activated Position	Field adjustable neutral position 0° to 360°
	23	Activated Position	Field adjustable: 0° to 45° from neutral (roller travel is not bound
			by the activation limit)
	24	Range of Travel	Bi-directional 0° to 90° from neutral
	25	Action	Non-latching
	26		
	27		
	28		
	29		
Options	30	Finish	Uncoated (standard) or epoxy coating (option E)
	31		nylon bearings with red powder coated steel roller (standard)
	32	Roller Material	nylon bearings with stainless steel roller (option SS)
			Heavy-duty ball bearings with red powder coated steel roller
	33		(option BB)
	34		
	35		
	36		
Certifications	37	UL Certification File	NMFT.E83971
	38	cUL Certification File	NMFT7.E83971
	39		
Manufacturer			Conveyor Components Company
			Division of Material Control, Inc.
		/(;\	130 Seltzer Road, PO Box 167
	40		Croswell, MI 48422 USA
			(810) 679-4211
		lacksquare	info@conveyorcomponents.com
			www.conveyorcomponents.com
Notes: 1 Typically used in pairs at each end of the conveyor to provide proper protection			

Notes: 1. Typically used in pairs at each end of the conveyor to provide proper protection.



