





	Total	Power	Signals	Weight(kg)	Power	Signals
		14A	2A		Faston	Faston
SVTS B 01-S-A-02/00	2	2	-	0,05	0.8x6.3	-
SVTS B 01-S-A-03/00	3	3	-	0,05	0.8x6.3	-
SVTS B 01-S-A-02/02	4	2	2	0,05	0.8x6.3	0.8x2.8

Contact material	precious metals
Faston 2A (mm)	0,8x6,3
Faston 14A (mm)	0,8x2,8
Dielectric strength	500VAC@60Hz,60s
Insulation resistance	$\geq 1000M\Omega/500Vdc$
Dynamic contact resistance	$<100m\Omega @6Vdc$ 50mA 5RPM
Operating Speed	400rpm
Temperature	-20°C ~ +80°C
Housing material	Engineering plastic
Shaft material	Engineering plastic
Protection degree	IP51
Bearings	steel ball bearings

TRATTAMENTO TREATMENT:		4		
		3	01/06/2016	Aggiornamento Part Number
		2	02/11/2015	Aggiunti valori di massa
		1	05/03/2013	Modifica specifiche elettriche
		0	12/10/2012	Prima emissione
MATERIALE MATERIAL:		REV. Nr	DATA/DATE	DESCRIZIONE/DESCRIPTION
		REV N°		
PESO WEIGHT		Tolleranze/Tolerances UNI EN 22768-1		
		FINE		
		MEDIA		x
		GROSSOLANA		
		MOLTO GROSSOLANA		
		DATE DATA 12/10/2012		SH. FG. 1
 		CHECK CONTR. AG		DRAW. DIS. AG
		FORM A3		
PROPERTY PROPRIETÀ SERVOTECNICA S.P.A. - VIA MAJORANA,4 - NOVA MILANESE(MB) - www.servotecnica.com				
DRAWING Nr. - DISEGNO N° 000-081				
CODICE SERVOTECNICA				