



T-Max® P, inserto per tornitura

Rombico 80°




	IC	RE	L	S	P										M					K				S				CODICE ANSI																																																																																																
					1515	1525	4205	4235	4315	4325	5015	GC30	1115	1125	2015	2025	2035	235	GC15	3005	3205	3210	3215	GC30	H13A	1105	1115		1125	GC15	H13A	S05F																																																																																												
	12	1/2			CODICE ISO CNMU 12 04 12-KM CNMU 12 06 12-KM																														CODICE ANSI CNMU 433-KM CNMU 443-KM																																																																																									
	12	1/2			CODICE ISO CNMU 12 04 12-PM CNMU 12 06 12-PM																														☆ ☆ ☆ ☆																														CNMU 433-PM CNMU 443-PM																																																											
	12	1/2			CODICE ISO CNMU 12 04 12-QM																														☆ ☆																														CNMU 433-QM																																																											
	12	1/2			CODICE ISO CNMG 12 04 08-SMR CNMG 12 04 12-SMR CNMG 12 04 16-SMR																														☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆																														☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆																														CNMG 432-SMR CNMG 433-SMR CNMG 434-SMR																													
	09	3/8			CODICE ISO CNMG 09 03 08-XM																														☆																														☆																														CNMG 322-XM																													
	12	1/2			CODICE ISO CNMG 12 04 04-XM CNMG 12 04 08-XM CNMG 12 04 12-XM																														☆ ☆ ☆ ☆ ☆																														☆ ☆ ☆ ☆ ☆																														CNMG 431-XM CNMG 432-XM CNMG 433-XM																													
	12	1/2			CODICE ISO CNMG 12 04 12-MRR CNMG 12 04 16-MRR																														☆ ☆ ☆ ☆																														☆ ☆ ☆ ☆																														CNMG 433-MRR CNMG 434-MRR																													
	16	5/8			CODICE ISO CNMG 16 06 12-MRR CNMG 16 06 16-MRR																														☆ ☆ ☆ ☆																														☆ ☆ ☆ ☆																														CNMG 543-MRR CNMG 544-MRR																													
	19	3/4			CODICE ISO CNMG 19 06 12-MRR CNMG 19 06 16-MRR CNMG 19 06 24-MRR																														☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆																														☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆ ☆																														CNMG 643-MRR CNMG 644-MRR CNMG 646-MRR																													

Per le dimensioni, vedere la chiave dei codici a pagina I14.



T-Max® P, inserto per tornitura

Rombico 80°



		CODICE ISO	P								M					K				S				CODICE ANSI						
			1515	1525	4205	4235	4315	4325	5015	GC30	1115	1125	2015	2025	2035	235	GC15	3005	3205	3210	3215	GC30	H13A		1105	1115	1125	GC15	H13A	S05F
Sgrossatura		12 1/2	CNMM 12 04 08-MR																											CNMM 432-MR
			CNMM 12 04 12-MR											*	*															CNMM 433-MR
			CNMM 12 04 16-MR											*	*															CNMM 434-MR
		16 5/8	CNMM 16 06 12-MR											*	*															CNMM 543-MR
			CNMM 16 06 16-MR											*	*															CNMM 544-MR
		16 5/8	CNMM 16 06 12-MR											*	*															CNMM 643-MR
			CNMM 16 06 16-MR											*	*															CNMM 644-MR
		19 3/4	CNMM 19 06 12-MR											*	*															CNMM 646-MR
			CNMM 19 06 16-MR											*	*															CNMM 866-MR
			CNMM 19 06 24-MR				*							*	*															
		12 1/2	CNMG 12 04 08-KRR															*	*	*										CNMG 432-KRR
			CNMG 12 04 12-KRR															*	*	*										CNMG 433-KRR
			CNMG 12 04 16-KRR															*	*	*										CNMG 434-KRR
		16 5/8	CNMG 16 06 12-KRR															*	*	*										CNMG 543-KRR
			CNMG 16 06 16-KRR															*	*	*										CNMG 544-KRR
		16 5/8	CNMM 16 06 12-WR			*	*	*																						CNMM 543-WR
			CNMM 16 06 16-WR			*	*	*																						CNMM 544-WR
		19 3/4	CNMM 19 06 16-WR			*	*	*																						CNMM 644-WR
		12 1/2	CNMM 12 04 08-WR			*	*	*																						CNMM 432-WR
			CNMM 12 04 12-WR			*	*	*																						CNMM 433-WR
	12 1/2	CNMG 12 04 08-PR			*	*	*	*																					CNMG 432-PR	
		CNMG 12 04 12-PR			*	*	*	*																					CNMG 433-PR	
		CNMG 12 04 16-PR			*	*	*	*																					CNMG 434-PR	
	16 5/8	CNMG 16 06 08-PR			*	*	*	*																					CNMG 542-PR	
		CNMG 16 06 12-PR			*	*	*	*																					CNMG 543-PR	
		CNMG 16 06 16-PR			*	*	*	*																					CNMG 544-PR	
		CNMG 16 06 24-PR			*	*	*	*																					CNMG 546-PR	
	19 3/4	CNMG 19 06 08-PR			*	*	*	*																					CNMG 642-PR	
		CNMG 19 06 12-PR			*	*	*	*																					CNMG 643-PR	
		CNMG 19 06 16-PR			*	*	*	*																					CNMG 644-PR	
	CNMG 19 06 24-PR			*	*	*	*																					CNMG 646-PR		
25 1	CNMG 25 09 24-PR			*	*	*	*																					CNMG 866-PR		
	12 1/2	CNMM 12 04 08-PR			*	*	*	*																					CNMM 432-PR	
		CNMM 12 04 12-PR			*	*	*	*																					CNMM 433-PR	
		CNMM 12 04 16-PR			*	*	*	*																					CNMM 434-PR	
	16 5/8	CNMM 16 06 08-PR			*	*	*	*																					CNMM 542-PR	
		CNMM 16 06 12-PR			*	*	*	*																					CNMM 543-PR	
		CNMM 16 06 16-PR			*	*	*	*																					CNMM 544-PR	
	19 3/4	CNMM 19 06 12-PR			*	*	*	*																					CNMM 643-PR	
		CNMM 19 06 16-PR			*	*	*	*																					CNMM 644-PR	
	CNMM 19 06 24-PR			*	*	*	*																					CNMM 646-PR		

Per le dimensioni, vedere la chiave dei codici a pagina I14.

