



PLUS 3P SX

WORKING CONDITIONS

Max working pressure _____ 8 bar (116 psi)
 Max working temperature _____ 45°C (113°F)
 Min working temperature _____ 4°C (39,2°F)

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Head and ring nut: reinforced polypropylene.
 Bowl: PET.
 O-ring: EPDM.
 Breather-valve: body polypropylene, o-ring EPDM.
 IN/OUT brass threads: CW 614 N brass.

PLUS 3P SX clear housings

HOUSINGS WITH BRASS BSP THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	THREADS	DIMENSIONS mm		
					A	B	C
RA107T111	MEDIUM PLUS 3P MFO SX TS	5"	1/2"	BRASS-BSP	191	133	130
RA107T411	MEDIUM PLUS 3P AFO SX TS	5"	3/4"	BRASS-BSP	191	133	130
RA107T711	MEDIUM PLUS 3P BFO SX TS	5"	1"	BRASS-BSP	197	145	130
RA109T111	JUNIOR PLUS 3P MFO SX TS	7"	1/2"	BRASS-BSP	241	133	130
RA109T411	JUNIOR PLUS 3P AFO SX TS	7"	3/4"	BRASS-BSP	241	133	130
RA109T711	JUNIOR PLUS 3P BFO SX TS	7"	1"	BRASS-BSP	247	145	130
RA111T111	SENIOR PLUS 3P MFO SX TS	10"	1/2"	BRASS-BSP	315	133	130
RA111T411	SENIOR PLUS 3P AFO SX TS	10"	3/4"	BRASS-BSP	315	133	130
RA111T711	SENIOR PLUS 3P BFO SX TS	10"	1"	BRASS-BSP	321	145	130
RA115T111	MASTER PLUS 3P MFO SX TS	20"	1/2"	BRASS-BSP	571	133	130
RA115T411	MASTER PLUS 3P AFO SX TS	20"	3/4"	BRASS-BSP	571	133	130
RA115T711	MASTER PLUS 3P BFO SX TS	20"	1"	BRASS-BSP	577	145	130

HOUSINGS WITH PLASTIC BSP THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	THREADS	DIMENSIONS mm		
					A	B	C
RA107T211	MEDIUM PLUS 3P MFP SX TS	5"	1/2"	PLASTIC-BSP	191	133	130
RA107T511	MEDIUM PLUS 3P APP SX TS	5"	3/4"	PLASTIC-BSP	191	133	130
RA107T811	MEDIUM PLUS 3P BFP SX TS	5"	1"	PLASTIC-BSP	197	145	130
RA109T211	JUNIOR PLUS 3P MFP SX TS	7"	1/2"	PLASTIC-BSP	241	133	130
RA109T511	JUNIOR PLUS 3P APP SX TS	7"	3/4"	PLASTIC-BSP	241	133	130
RA109T811	JUNIOR PLUS 3P BFP SX TS	7"	1"	PLASTIC-BSP	247	145	130
RA111T211	SENIOR PLUS 3P MFP SX TS	10"	1/2"	PLASTIC-BSP	315	133	130
RA111T511	SENIOR PLUS 3P APP SX TS	10"	3/4"	PLASTIC-BSP	315	133	130
RA111T811	SENIOR PLUS 3P BFP SX TS	10"	1"	PLASTIC-BSP	321	145	130
RA115T211	MASTER PLUS 3P MFP SX TS	20"	1/2"	PLASTIC-BSP	571	133	130
RA115T511	MASTER PLUS 3P APP SX TS	20"	3/4"	PLASTIC-BSP	571	133	130
RA115T811	MASTER PLUS 3P BFP SX TS	20"	1"	PLASTIC-BSP	577	145	130

HOUSINGS WITH PLASTIC NPT THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	THREADS	DIMENSIONS mm		
					A	B	C
RA107T513	MEDIUM PLUS 3P APP NPT SX TS	5"	3/4"	PLASTIC-NPT	191	133	130
RA107T813	MEDIUM PLUS 3P BFP NPT SX TS	5"	1"	PLASTIC-NPT	197	145	130
RA109T513	JUNIOR PLUS 3P APP NPT SX TS	7"	3/4"	PLASTIC-NPT	241	133	130
RA109T813	JUNIOR PLUS 3P BFP NPT SX TS	7"	1"	PLASTIC-NPT	247	145	130
RA111T610	SENIOR PLUS 3P APP NPT SX TS	10"	3/4"	PLASTIC-NPT	315	133	130
RA111T611	SENIOR PLUS 3P BFP NPT SX TS	10"	1"	PLASTIC-NPT	321	145	130
RA115T611	MASTER PLUS 3P APP NPT SX TS	20"	3/4"	PLASTIC-NPT	571	133	130
RA115T813	MASTER PLUS 3P BFP NPT SX TS	20"	1"	PLASTIC-NPT	577	145	130

HOUSINGS WITH PLASTIC BSP THREADS

CODE	MODEL	SUITABLE CARTRIDGE	IN/OUT	THREADS	DIMENSIONS mm		
					A	B	C
RA107T215	MEDIUM PLUS 3P MMP SX TS	5"	1/2"	PLASTIC-BSP	191	175	130
RA107T515	MEDIUM PLUS 3P AMP SX TS	5"	3/4"	PLASTIC-BSP	191	175	130
RA107T815	MEDIUM PLUS 3P BMP SX TS	5"	1"	PLASTIC-BSP	197	175	130
RA109T215	JUNIOR PLUS 3P MMP SX TS	7"	1/2"	PLASTIC-BSP	241	175	130
RA109T515	JUNIOR PLUS 3P AMP SX TS	7"	3/4"	PLASTIC-BSP	241	175	130
RA109T815	JUNIOR PLUS 3P BMP SX TS	7"	1"	PLASTIC-BSP	247	175	130
RA111T215	SENIOR PLUS 3P MMP SX TS	10"	1/2"	PLASTIC-BSP	315	175	130
RA111T515	SENIOR PLUS 3P AMP SX TS	10"	3/4"	PLASTIC-BSP	315	175	130
RA111T815	SENIOR PLUS 3P BMP SX TS	10"	1"	PLASTIC-BSP	321	175	130
RA115T215	MASTER PLUS 3P MMP SX TS	20"	1/2"	PLASTIC-BSP	571	175	130
RA115T515	MASTER PLUS 3P AMP SX TS	20"	3/4"	PLASTIC-BSP	571	175	130
RA115T815	MASTER PLUS 3P BMP SX TS	20"	1"	PLASTIC-BSP	577	175	130

