## EK 60/22 Battery powered hydraulic crimping tool 6 - 300 mm<sup>2</sup>











- ▶ Large crimping range up to 300 mm²
- ► Fast crimp cycles due to Automatic Retraction Stop (ARS)
- ▶ All tool data in view thanks to display and ipress app

## **Characteristics**

- Choose your battery system: Bosch or Makita
- All data can be easily read via Bluetooth
- Closed head, flip top style, rotatable
- Quality assurance via visual and audible signals in case of error
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination

Makita battery 18 V / 4.0 Ah, Li-lon

- Simple and safe: Automatic retraction when operation is complete
- Automatic retract stop (ARS) for positioning control in case of multiple crimps
- Always ready-to-use thanks to battery charge and service display

22-series interchangeable dies, narrow crimping

Technical data				
Crimping force	60 kN			
Hub	17 mm			
Crimping range	6 - 300 mm²			
Crimping cycle	3 s to 5 s (depending on crimp cross-section)			
Charging time	45 min.			
Weight incl. battery	4.4 kg			
Ambient temperature	-10 °C up to +40 °C			
Item		Part No. Bosch	Part No. Makita	
Battery powered hydraulic crimp	oing tool 6 - 300 mm²	EK6022CFB	EK6022CFM	
Battery powered hydraulic crimp Scope of supply	oing tool 6 - 300 mm²	EK6022CFB	EK6022CFM	Page
		EK6022CFB RALB2EU	EK6022CFM	Page 493
Scope of supply	on		EK6022CFM	
Scope of supply Bosch battery 18 V / 5.0 Ah, Li-le	on -lon battery	RALB2EU	EK6022CFM	493
Scope of supply Bosch battery 18 V / 5.0 Ah, Li-le Bosch quick-charger for 18 V Li-	on -lon battery lon	RALB2EU		493 494
Scope of supply Bosch battery 18 V / 5.0 Ah, Li-le Bosch quick-charger for 18 V Li- Makita battery 18 V / 4.0 Ah, Li-	on -lon battery lon	RALB2EU	RAL40	493 494 492
Scope of supply Bosch battery 18 V / 5.0 Ah, Li-le Bosch quick-charger for 18 V Li- Makita battery 18 V / 4.0 Ah, Li- Makita battery 18 V / 3.0 Ah, Li-	on -lon battery lon	RALB2EU LGLB1EU	RAL40 LGL1	493 494 492







RAL40

492